

# The Use of GPS and Numerical Improvements in Aeromagnetic Compensation


Ruizhong Jia, Ross Groom, *PetRos EiKon Inc*

Bob Lo, *BHL Services*

*Society of Exploration Geophysicists, Denver, 2004*

## TOPICS

- Background
- The role of highpass filtering
- The use of synthetic aircraft magnetic effects
- Compensation using GPS data



# Motivation

- Modern systems acquire very high quality data
  - Aircraft are magnetic – source of interference
  - Interference varies with attitude
- *Compensation is a limiting factor in obtaining highly accurate data*



# Theory

## Three sources of magnetic interference:

- Permanent: its angle with earth's field changes
- Induced: polarity and magnitude change
- **Eddy-Current: currents caused by the aircraft's conductive structures moving in the earth's magnetic field which are proportional to the time change rate of change of magnetic flux through some parts of aircraft**



## Leliak 1961, 18-term interference model

$$\begin{aligned}
 H_T = & c_1 \cos X + c_2 \cos Y + c_3 \cos Z + \\
 & + \left\| \vec{H} \right\| \{ c_4 \cos^2 X + c_5 \cos X \cos Y + c_6 \cos X \cos Z + \\
 & \quad + c_7 \cos^2 Y + c_8 \cos Y \cos Z + c_9 \cos^2 Z \} + \\
 & + \left\| \vec{H} \right\| \{ c_{10} \cos X (\cos X)' + c_{11} \cos X (\cos Y)' + c_{12} \cos X (\cos Z)' + \\
 & \quad + c_{13} \cos Y (\cos X)' + c_{14} \cos Y (\cos Y)' + c_{15} \cos Y (\cos Z)' + \\
 & \quad + c_{16} \cos Z (\cos X)' + c_{17} \cos Z (\cos Y)' + c_{18} \cos Z (\cos Z)' \} = \sum_{i=1}^{18} c_i a_i
 \end{aligned}$$


✓  $c_i, i=1,3$  - permanent

✓  $c_i, i=4,9$  - induced

✓  $c_i, i=10,18$  - induced EM

✓  $\vec{H}$  total field vector

✓  $\cos X, \cos Y, \cos Z$  directional cosines of aircraft's axes and  $\vec{H}$ , usually obtained via 3-component vector fluxgate magnetometers



# Filtration and Solvers: The Issue of Noise

## Noise Sources

- Local gradient of total field
- Geologic noise
- Micropulsation, etc

## Purpose of Filtration

- Restrict the frequency bandwidth of the data to be centered around the primary frequency modes for the aircraft maneuvers


## Techniques for Solving the Linear Equation System

- Singular Value Decomposition (SVD)
- Ridge Regression




## Compensation Box

- ✓ Comp box is usually flown above 3000m
- ✓ Flight Headings are along the heading of survey and tie line flight headings
- ✓ Series of maneuvers to determine the coefficients
- ✓ Apply coefficients of compensation box to survey data with appropriate heading




# High Pass Filtering VS. Compensation

Helicopter Example    ■ Heading: WNW




Measured fluxgate Channels



Measured Total field




## Filtration is necessary




Red: Measured Total field

Blue: compensated without filtration



# Compensation Results with Different Filters




## Line-to-Line Compensation

- Red: measured total field (FOM=472)
- Blue: compensated with tight filter (FOM=94)
- Green: compensated with wider filter (FOM=67)

(Figure of Merit (FOM): sum of peak-to-peak levels)



## Compensation Results



### Zoom-in display

- Red: measured total field (FOM=60)
- Blue: compensated with tight filter (FOM=17)
- Green: compensated with wider filter (FOM=3)



# Fixed Wing GPS Compensation






## Three GPS receivers were installed on wingtip, fuselage and stinger


- Field tests were done with 3 Novatel Millennium geodetic grade, dual frequency GPS's on Terraquest's Navajo
- GPS's were sampled at 10 Hz
- GPS base station was 40 to 70 kms away
- base station a Novatel Millennium sampled at 10 Hz
- differential corrections done with WayPoint software



# Real Flight




# Measured Fluxgate




- **Red: transverse**
- **Blue: longitudinal**
- **Green: vertical**




# Compensation Results with Measured Fluxgate



Red: measured (FOM = 292), Blue(FOM=97)



Red: measured (FOM = 72), Blue(FOM=0.94)




*Petros Eikon*


# GPS Based Compensation

## Steps for estimating fluxgate data utilizing GPS information

1. Determine the orientations of aircraft's axes in UTM coordinate system
2. Use IGRF inclination and declination of local field to calculate the fluxgate data



- O-XYZ: UTM coordinate system
- O-uvw: aircraft reference system
- Blue: vectors are generated with GPS data, which are invariant wrt. aircraft system O-uvw





# Synthetic Testing

## Perspective view of the a sample block model of the “aircraft”

▪ **Permanent:** blue blocks stand for two magnetic dipoles, one on each wing

▪ **Induced:** red blocks are 2 thin rectangular prisms representing the two wings and another long box type prism to represent the fuselage


▪ **Eddy-current fields:**  
Calculated by the time variation of the coupling of the tow prism structures representing the wings with the earth's field



# Synthetic Fluxgate Channels

Local Field:

- Inclination 71.3 degrees
- Declination: 11 degrees west to the north




Vertical Fluxgate Channel


▪ Red: measured

▪ Blue: synthetic

*Petros Eikon*




# Synthetic Fluxgate Channels




## Longitudinal Fluxgate Channel

- Red: measured
- Blue: synthetic




*Petros Eikon*

# Synthetic Fluxgate Channels




Transverse Fluxgate Channel

- Red: measured
- Blue: synthetic



*Petros Eikon*


# Compensation Results with Measured Fluxgate



Red: measured (FOM = 292)


Blue: compensated with measured Fluxgate (FOM=97)

Green: compensated with synthetic Fluxgate (FOM=94)



*Petros Eikon*

# Compensation Results with Measured Fluxgate




Zoom-in display

Red: measured (FOM = 72)

Blue: compensated with measured Fluxgate (FOM=0.94)

Green: compensated with synthetic Fluxgate (FOM=0.9)




*Petros Eikon*

# Conclusions

- ❖ Based on a function calculating Figure of Merit (FOM), an optimum filtration can be selected.
- ❖ Aeromagnetic compensation can be accomplished using 3 GPS sensors mounted on aircraft
- ❖ Capable of building synthetic the aircraft's magnetic effects based on GPS information

## Direction:

- ❖ Compensate Fluxgate data utilizing GPS information



# Acknowledgements

- To the Ontario Geological Survey and Terraquest releasing the raw aeromagnetic data for this research,
- To Terraquest for supplying their Navajo for the airborne testing
- To the Province of Ontario for partial funding of the research
- To Barrie Leach and Nelson Bradley (NRC-Canada) for their helpful discussions and suggestions

